

Hybrid Additive

Description

Additive specially developed for the latest hybrid engines. With outstanding cleaning effect adapted to the engine technology. Removes deposits and protects against corrosion. Stabilizes the fuel and protects against aging and oxidation.

Hybrid vehicles are characterized by the lowest fuel consumption and, in some cases, purely electric driving. This results in the gasoline engine frequently being operated when cold, as well as being started and stopped often. The fuel also remains in the tank for a relatively long time.

Properties

- optimum stability to aging
- good corrosion protection
- prevents the build-up of deposits
- stabilizes the fuel over extended service time
- suitable for engines with intake-manifold injection and direct injection
- cleans the injection system and the combustion chamber

Technical data

Form	liquid
Color / appearance	yellow
Odor	characteristic
Density at 20 °C	0,815 g/ml
Flash point	>61 °C
Shelf life in original sealed container	60 months

Areas of application

Suitable for all hybrid vehicles with gasoline engine. To be added directly into the fuel tank. 250 ml sufficient for up to 75 l of gasoline (dosage 1:300).

Application

Add the additive directly to the tank. One can is sufficient for 75 l of gasoline.

Available pack sizes

250 ml Can sheet metal	1001 DE-EN-ES-IT-PT
250 ml Can sheet metal	20978 DA-EN-FI-NO-SV
250 ml Can sheet metal	21697 AUEN-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

